

Wall and façade cladding — of high-pressure laminate Vägg- och fasadbeklädnad – av högtryckslaminat

BSAB PR:KA

# Façade boards, marmoroc composite

Façade boards with outer surface of waterproofed wood veneer for exterior and interior façades. A complete façade system, including with façade insulation.

## **Product description**

Parklex brand façade boards have an outer surface of wood veneer on a core of cellulose fibres and phenolic resin, which is compressed under high pressure and heat. The façade boards have great impact resistance and withstand strong sunlight, rain, wind, snow and frost. Boards with a curved radius, slits or perforations in various patterns can be ordered. The boards have fire resistance classification Bs1-d0 and FIRE 105 and environmental classification according to Basta, Byggvarudeklarationen and Sunda Hus.

## **MEASUREMENTS - WEIGHT**

Format:  $2,440\times1,220$  mm. Special formats max  $2,750\times1,220$  mm, can be ordered for some veneers.

Thickness: 3, 6, 8, 10, 12, 14, 18, 20 and 22 mm.

Space requirement: 26–50 mm including fitting profile.

The boards weigh c. 1.35 kg/m $^2$ /mm or c. 13.5 kg/m $^2$  for 10 mm board.

#### **APPFARANCE**

The outer surface has the natural and varied grain and colour of the veneer. There are 8 different colours for exterior façades and 26 colours for interior cladding (façades and ceilings).

## **Properties**

#### FIRE

Meets Bs1-d0 and FIRE 105.

### **ENVIRONMENT**

Environmental classification according to Basta, Byggvarudeklarationen and Sunda Hus.

## Planning guidelines

The façade sheets are fastened with screws or glue to metal or timber rails, so as to create a 20–30 mm air space between board and substrate. Concealed fixing for screws is available with thicknesses of 10 mm and above. A complete insulation system is available for exterior façade insulation (see separate report on the page on Marmoroc Support System).

Assembly instructions and detail drawings for termination to doors, windows, corners, foundation, eaves etc. can be ordered.

### **Marmoroc AB**

ADRESS: Box 274, 731 26 Köping

TEL: 0221-366 00 E-POST: info@marmoroc.com WEBB: www.marmoroc.com







Façade sheets with a sawed pattern



Office, central Stockholm

CONTD. >



CONTD.

Wall and façade cladding — of high-pressure laminate Vägg- och fasadbeklädnad – av högtryckslaminat

BSAB PR:KA



School, Kungsbacka



Window detail



Balconies, façades with concealed fixings and ceiling with visible screw fixing.



Travel centre Örnsköldvik, walls and ceiling



Landvetter travel centre



Curved façade, Landvetter travel centre



Entrance façade

www.byggtjanst.se © SVENSK BYGGTJÄNST